



Max. Gross Machine Weight	85,000 kg
Net Machine Weight	40,000 kg
Payload	45,000 kg
Engine	HL13200
Rated Power	480 kW (644 hp / 653 ps) @ 1,050 rpm
Max. Speed	55 km/h
Reverse Speed	10 km/h
Struck Capacity	22 m ³
Heaped Capacity (SAE 2:1)	30 m ³

DR50C-E ELECTRIC MINING TRUCK

DR50C-E SPECIFICATIONS >>>

DRIVE MOTOR

Motor Type	Permanent magnet synchronous motor
Rated / Peak Power	480 kW (644 hp / 653 ps) / 1,200 kW (1,609 hp / 1,632 ps)
Rated / Peak Speed	1,050 / 3,000 rpm
Cooling Mode	Water

OIL PUMP MOTOR

Rated / Peak Power	60 kW (80 hp / 82 ps) / 110 kW (148 hp / 150 ps) @ 60 s
Rated / Peak Torque	275 kW (369 hp / 374 ps) / 500 kW (671 hp / 680 ps) @ 60 s
Cooling Mode	Water

WEIGHT DISTRIBUTION

Empty Load	Front axle: 49% Rear axle: 51%
Full Load	Front axle: 36% Rear axle: 64%
Working Environment Temperature	-40 ~ 55°C
Relative Humidity of Working Environment	0-100%
Continuous Climbing Capacity (8% Gradient, 2% Rolling Resistance)	Load: > 17 km/h Unload: > 36 km/h
Max. Gradeability	≥30%

POWER BATTERY

Battery Type	Lithium iron phosphate
Battery Capacity	423 kWh
Voltage Platform	618 V
Cooling Mode	Water
Heating Mode	Membrane + Water

BRAKING

Braking Type	Service brake / Parking / Emergency / Electric braking
Service Brake Type	Front dry and rear wet
Braking Distance	≤12.3 m
Service Braking Capacity (Full Load)	>30%
Parking Braking Capacity (Full Load)	>15%

TIRE AND RIM

Tire Size	21.00-35/E4
Rim	15.00/3.0-35

CHARGE

Charge Mode	Double DC
Charging Current	500 A
Charging Power	360 kW (483 hp / 489 ps)
Charging Time (SOC20%)	60 min

STEERING

Steering System	Full hydraulic dynamic load sensing
Turning Radius	≤9,228 mm
Max. Steering Angle	38°

DRIVE AXLE

Mode	Heavy duty, fully floating axle shaft
Suspension	Nitrogen gas / Oil suspension
Speed Ratio	20.5

DIMENSIONS

Overall Length	8,922 mm
Overall Width	5,345 mm
Overall Height	4,243 mm
Loading Height	3,477 mm

LIFTING SYSTEM

Lifting Mode	External double cylinder frame
Lifting Time	≤15 s
Lowering Time	≤12 s

